CF010-2 X



CF010-2 X*

CF010-2 X is a super smooth, dimensionally stable CHEMFAB® PTFE-coated glasscloth. It is specifically designed to be non-porous and free of microcracking and offers improved performance and durability due to the final outer layers which are specifically configured to yield improved wearing characteristics.

This product is typically used as a conveyor belt in extremely "sticky" or mildly abrasive environments such as food contact grilling and foam manufacturing.

Typical Properties

Property	Value	Value	Test Method
Weight	g/m²	580	FTMS 191A-5041
Thickness	mm	0.275	FTMS 191A-5030
Tensile Strength	N/cm	520 x 400	FTMS 191A-5102
Trap Tear Strength	N	35 x 30	FTMS 191A-5136
Dielectric Strength	kV	8.4	ASTM D149-81
PTFE Content	%	66	-
Temperature Resistance	°C	-150 to +260	-
Standard Width	mm	1000, 1525, 2000	-

^{*} Formerly EHV-10 CF CC, Tygaflor 128AAA

Saint-Gobain Performance Plastics Ireland

Kilrush Business Park, Kilrush, Co. Clare, V15 NW27 Tel: +353 65 90 80 170

Saint-Gobain Performance Plastics Germany

Tel: +49 (0) 2203 956-362

Saint-Gobain Performance Plastics Tygaflor Ltd United Kingdom

Tel: +44 (0) 1706 746900

Saint-Gobain Performance Plastics Poland

Tel: +48 (63) 261 7252

chemfab@saint-gobain.com

www.chemfab.com

CHEMFAB® is a registered trademark ©2017 Saint-Gobain Performance Plastics Corporation

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof.

Saint-Gobain Performance Plastics does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s). Nothing in this disclaimer limits Saint-Gobain Performance Plastics' liability for death or personal injury due to its negligence

