

SRF110-2 TR

SRF110-2 TR comprises specially treated PTFE-coated woven fiberglass reinforcement: This CHEMFAB® product is specifically designed to be extremely flexible and tear resistant and can be easily fabricated. SRF110-2 TR was designed to provide a smoother surface with Superior release and a higher resistance to mechanical damage than regular products.

Typical Properties

Property	Units	Value	Test Method
Weight	g/m ²	490	FTMS 191A-5041
Thickness	mm	0.245	FTMS 191A-5030
Tensile Strength	N/cm	540 x 370	FTMS 191A-5102
Trap Tear Strength	N	95 x 75	FTMS 191A-5136
PTFE Content	%	59	
Temperature Resistance	°C	-150 to +260	-
Standard Width	mm	1000	-

Saint-Gobain Films & Fabrics Ireland

Kilrush Business Park,
Kilrush, Co. Clare, V15 NW27
Tel: +353 65 90 80 170

Saint-Gobain Films & Fabrics Germany

Tel: +49 (0) 215 460 238

Saint-Gobain Films & Fabrics Poland

Tel: +48 (63) 261 7252

chemfab@saint-gobain.com
www.chemfab.com

CHEMFAB® is a registered trademark of Saint-Gobain Films & Fabrics
Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Films & Fabrics warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof.
Saint-Gobain Films & Fabrics does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s).
Nothing in this disclaimer limits Saint-Gobain Films & Fabrics' liability for death or personal injury due to its negligence

Valid 07/2020 Supersedes all previous versions
PDS.SRF110-2TR(SI).0720.EU.F&F