

CF210-1 AS*

CF210-1 AS is a Standard Grade CHEMFAB® PTFE-coated woven glass fabric with an anti-static coating. It provides excellent release properties as well as chemical and wear characteristics over wide temperature ranges where static dissipative properties are required.

Typical applications include packaging, release sheets for press lamination and food processing.

Typical Properties

Property	Value	Value	Test Method
Weight	g/m ²	490	FTMS 191A-5041
Thickness	mm	0.235	FTMS 191A-5030
Tensile Strength	N/cm	420 x 380	FTMS 191A-5102
Trap Tear Strength	N	30 x 35	FTMS 191A-5136
PTFE Content	%	58	-
Surface Resistivity	Ω/sq	<1 x 10 ⁶	ASTM D257-78
Temperature Resistance	°C	-150 to +260	-
Standard Width	mm	1525	-

* Formerly CF 200-10 AS

**Saint-Gobain Performance Plastics
Ireland**

Kilrush Business Park,
Kilrush, Co. Clare, V15 NW27
Tel: +353 65 90 80 170

**Saint-Gobain Performance Plastics
Germany**

Tel: +49 (0) 2203 956-362

**Saint-Gobain Performance Plastics
Tygaflo Ltd
United Kingdom**

Tel: +44 (0) 1706 746900

**Saint-Gobain Performance Plastics
Poland**

Tel: +48 (63) 261 7252

chemfab@saint-gobain.com

www.chemfab.com

CHEMFAB® is a registered trademark ©2017 Saint-Gobain Performance Plastics Corporation

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof.

Saint-Gobain Performance Plastics does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s). Nothing in this disclaimer limits Saint-Gobain Performance Plastics' liability for death or personal injury due to its negligence

Valid 03/2017 • Supersedes all previous versions
PDS.CF210-1AS.0317.EU.CFMC

