

## CORETECH® Flueflex1000 BF

Flueflex1000 BF is a CORETECH® material based on a high strength woven fibreglass substrate with excellent mechanical strength and flexibility that is coated with a matrix of fluoropolymer resins and then laminated on one side with a multi-layer cast PTFE film for extra chemical and permeation resistance.

Flueflex1000 BF combines the properties of outstanding mechanical strength with zero porosity and is specifically designed for use in wet and dry flue gas conditions in flexible expansion joints.

### Typical Properties

Property	Value	Test Method
Width	1540 mm	-
Weight	2000 g/m <sup>2</sup>	FTMS 191A-5041
Thickness	1.200 mm	FTMS 191A-5030
Tensile Strength	1900 x 1700 N/cm	FTMS 191A-5102
Trap Tear Strength	800 x 900 N	FTMS 191A-5136
Colour of Coated Side	Tan/Light Brown	-
Colour of Laminated Side	Black	-
Cast PTFE Film Thickness	0.100 mm	FTMS 191A-5030
Temperature Resistance	-150 to +300°C	-

**Saint-Gobain Performance Plastics**  
 Kilrush Business Park,  
 Kilrush, Co. Clare, V15 NW27  
 Telephone: +353 65 90 80 170

[chemfab@saint-gobain.com](mailto:chemfab@saint-gobain.com)

[www.coretechprotection.com](http://www.coretechprotection.com)

CORETECH® is a registered trademark ©2017 Saint-Gobain Performance Plastics Corporation

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof.

Saint-Gobain Performance Plastics does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s). Nothing in this disclaimer limits Saint-Gobain Performance Plastics' liability for death or personal injury due to its negligence

Valid 07/2017 • Supersedes all previous versions  
 PDS.CTFLUEFLEX1000BF.0717.EU.CFMC

