

SP010-2 X*

SP010-2 X is a super smooth, dimensionally stable, premium quality CHEMFAB® PTFE-coated glasscloth which provides excellent release properties and superior chemical resistance over wide temperature ranges.

This product is typically used in food processing (e.g. contact grilling) and polymer processing applications and has been specifically developed to provide longer life and higher resistance.

Typical Properties

Property	Value	Value	Test Method
Weight	g/m ²	560	FTMS 191A-5041
Thickness	mm	0.260	FTMS 191A-5030
Tensile Strength	N/cm	530 x 410	FTMS 191A-5102
Trap Tear Strength	N	40 x 30	FTMS 191A-5136
Dielectric Strength	kV	7.7	ASTM D149-81
PTFE Content	%	64	-
Temperature Resistance	°C	-150 to +260	-
Standard Width	mm	1000	-

* Formerly CF 100-10 CF 01

Saint-Gobain Performance Plastics Ireland

Kilrush Business Park,
Kilrush, Co. Clare, V15 NW27
Tel: +353 65 90 80 170

Saint-Gobain Performance Plastics Germany

Tel: +49 (0) 2203 956-362

Saint-Gobain Performance Plastics Tygaflor Ltd United Kingdom

Tel: +44 (0) 1706 746900

Saint-Gobain Performance Plastics Poland

Tel: +48 (63) 261 7252

chemfab@saint-gobain.com

www.chemfab.com

CHEMFAB® is a registered trademark ©2017 Saint-Gobain Performance Plastics Corporation

Limited Warranty: For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof.

Saint-Gobain Performance Plastics does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s). Nothing in this disclaimer limits Saint-Gobain Performance Plastics' liability for death or personal injury due to its negligence

Valid 03/2017 • Supersedes all previous versions
PDS.CFSP010-2X.0317.EU.CFMC

